



Frēzējuma dziļums = dotais dziļums + min. 1 mm

Frästiefe = angegebene Tiefe + min. 1 mm

Fräser ϕ 16 mm Frēze ϕ 16 mm
Anlaufring ϕ 27 mm Frēzes gredzens ϕ 27 mm

Artikula numurs iepiests uz pretplāksnes aizmugures
Artikel- Nr. auf der Rückseite geprägt
Pielaides regulējums pēc ISO 8015
Tolerierung nach ISO 8015

Pos. 3 in Pos. 2 einlegen
Pos. 2 und Pos. 1 mit Pos. 4 verschrauben

Poz. 3 ievietot poz. 2.

Poz. 2 un poz. 1 saskrūvēt ar poz. 4

4	Senkschraube DIN 7991-M4x12	3	9.999.03359		
3	Rd__Excenter	2	9.714.00090		
2	Schliesskasten komplett	1	7.880.00052		
1	Lappen- Schliessblech	1	9.872.20539		
Pos	Benennung	Stck	PDM-Nr.	Bemerk	
Qty.	Type of Modification	ANT	Drawn	Approved	
		Y7037A		Date	
Volume /mm ³	Weight/g	Material-No.	Item-No.	Tool-No.	
23305	109,919		3630-752QR		
		Tolerance	Part-Description		
		ISO 2768 mK	Flach-Schliessblech		
Scale	Additional Notice				
1 : 1					
Drawn	M. Müller-Bachem	KFV	Document No.	Doc. Part No.	
Date	07.03.2017		7.872.20540	000	Revision 00
Appr.	P. Thode		Replacement for :	Test procedure	Status
Date	13.03.2017		Replaced by :		20
				Size	
				A3	