








Fitting for top-running wooden doors up to 120 kg (264 lbs.), with surface mounted running track or running track flush with the ceiling. Optionally with soft and self closing mechanism. Wall or ceiling mounting. Minimal installation height.

Product highlights


-  **Aesthetics** Low installation height – only minimal gap between door and running track
-  **Productivity** Interlocking of the suspension at the front edge is possible

Technical specifications

-  Max. 120 kg (264 lbs.)
-  Max. 4000 mm (13'1 15/32")
-  Max. 3000 mm (9'10 1/8")
-  35–80 mm (1 3/8" to 3 5/32")










Installation examples




Set for 1 wooden door up to 120 kg (264 lbs.)

	No.
Hawa Junior 120 B, for 1 door	25908
Hawa Junior 120 B, with 2 track stoppers, for 1 door	26042


Set consisting of:

	25908	26042	No.
 Two-wheeled running gear, M12, plastic wheels	2	2	25900
 Track stopper, with adjustable retention spring	1	2	14858
 Suspension profile, with plate M12	2	2	14934
 Cover cap for glass suspension profile, plastic, anthracite	2	2	20907
 Bottom guide, zero tolerance, groove width 10 mm (13/32"), plastic black	1	1	14427
 Screw-on rubber door stop	1	1	10629
 Suspension assembly locking wrench	1	1	14861

Running tracks


	mm (inch)	No.
	2,500 (8' 2 7/16")	14866
	3,000 (9' 10 1/8 ")	14867
	4,000 (13' 1 15/32")	14868
	6,000 (19' 8 7/32")	14869
	cut to size	14871

Guide tracks


	mm (inch)	No.
	1,300 (4' 3 3/16")	14540

Soft close SoftMove 120




For soft closing in opening and closing direction order 2 sets.

	No.
 Soft close SoftMove 120	25988

Angled profiles for wall mounting






	mm (inch)	No.
	4,000 (13' 1 15/32")	25327
	6,000 (19' 8 7/32")	25328
	cut to size	25329

Individual components to angled profile

	No.
 Set for wall mounting, track length up to 2000 mm (6' 6 3/4 "), 10-piece set	19041
 Cover cap to angled profile, metal, chrome-plated, matt, suitable to both sides	25335
 Connecting pins to profiles, 2-piece set	21347






Hawa Adapto 120 concrete casting system, without fixed glazing

	No.
Inset profile for concrete surfaces Hawa Adapto 120, without fixed glass, 3000 mm (9'10 1/8")	20218
Inset profile for concrete surfaces Hawa Adapto 120, without fixed glass, 4000 mm (13'1 15/32")	20219






Set consisting of:	mm (inch)			No.
		20218	20219	
 Inset profile for concrete surfaces, without fixed glass, aluminum	3,000 (9' 10 1/8 ")	1		20093
 Polystyrene insert, 1000 mm (3'3 1/4 "), without fixed glass	1,000 (3' 3 3/8 ")	3	4	19419
 Assembly clips, without fixed glass plastic, black		4	5	19346
 Cover cap, without fixed glass, plastic, gray		2	2	19368
 Inset profile for concrete surfaces, without fixed glass, aluminum	4,000 (13' 1 15/32")		1	20091

Assembly set for Hawa Adapto 120

	No.
Assembly set, with countersunk head screw, length up to 2500 mm (8'2 7/16")(8'2 7/16")	22841
Assembly set, with countersunk head screw, length 2501–4000 mm (8'2 15/32"–13'1 15/32")	22842
Assembly set, with countersunk head screw, length 4001–6000 mm (13'1 17/32"– 19'8 7/32")	22843


Set consisting of:					No.
		22841	22842	22843	
 Distance plate, plastic, 1 mm (1/32")	2	2	3	19398	
 Distance plate, plastic, 2 mm (3/32")	2	2	3	19399	
 Distance plate, plastic, 3 mm (1/8")	2	2	3	19400	
 Distance plate, plastic, 5 mm (3/16")	4	4	6	19401	
 Special countersunk screws, 6x21 mm, 10-piece set	1	2	3	22844	

Accessories

	No.
 Cover cap, chrome-plated, matt, suitable to both sides	25332
 Bottom door stopper, with centering, stainless steel look	21473
 Bottom door stopper, with centering, chrome-plated, matt	20773
 Hawa assembly wedge, for 1 door	15770
 Bottom guide, rattle proof, groove width 10 mm (13/32"), plastic, black, 10-piece set	25958


Hawa Junior 120 angled profile for wall mounting

The intelligent wall mounting with the new angled profile for Hawa Junior running tracks for a door weight of up to 120 kg (264 lbs.).




Hawa Adapto 120 concrete casting system

The Hawa Adapto 120 concrete casting system can be easily and efficiently integrated into the building shell and allows Hawa Junior 120 running tracks to be installed flush with the ceiling.




Hawa Confort 120

The convenient solution to an old problem. Inadequate fastening options in brittle sub-floors or in the area of floor heating. This bottom guide is mounted on the wall.





Mounting wedge



SoftMove 120 soft closing mechanism

Completely integrated into the running track, the SoftMove decelerates sliding doors and draws them into their final position.



Accessories

- Hawa Junior bottom guides for wall mounting from page 508
- Lock solutions from page 511
- General accessories from page 518

Planning/execution

Further information about the product can be found on www.hawa.com.